

Package ‘selectKSigs’

April 18, 2025

Type Package

Title Selecting the number of mutational signatures using a
perplexity-based measure and cross-validation

Depends R(>= 3.6)

Imports HiLDA, magrittr, gtools, methods, Rcpp

Suggests knitr, rmarkdown, testthat, BiocStyle, ggplot2, dplyr, tidyr

Version 1.21.0

Date 2021-10-18

Description A package to suggest the number of mutational signatures in a
collection of somatic mutations using calculating the cross-validated
perplexity score.

URL <https://github.com/USCbiostats/selectKSigs>

BugReports <https://github.com/USCbiostats/HiLDA/selectKSigs>

License GPL-3

biocViews Software, SomaticMutation, Sequencing, StatisticalMethod,
Clustering

RoxygenNote 7.1.2

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/selectKSigs>

git_branch devel

git_last_commit 6688702

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-04-17

Author Zhi Yang [aut, cre],
Yuichi Shiraishi [ctb]

Maintainer Zhi Yang <zyang895@gmail.com>

Contents

calcPMSLikelihood	2
Calculate_Likelihood_test	3
convertFromTurbo_F	3
convertFromTurbo_Q	4
convertToTurbo_F	4
convertToTurbo_Q	5
cv_PMSignature	5
getBG	6
getCounts	6
getExposures	7
getFeatures	7
getFeatureVec	8
getK	8
getLL	9
getLogLikelihoodC	9
getSamplelist	10
getSamplelistG	10
getSignatures	11
getTranscription	11
select_kth_fold	12
splitG	12
Index	13

calcPMSLikelihood	<i>A function for calculating the log-likelihood from the data and parameters</i>
-------------------	---

Description

A function for calculating the log-likelihood from the data and parameters

Usage

calcPMSLikelihood(p, y)

Arguments

- | | |
|---|--|
| p | this variable includes the parameters for mutation signatures and membership parameters |
| y | this variable includes the information on the mutation features, the number of mutation signatures specified and so on |

Value

a value

`Calculate_Likelihood_test`*Output the maximum potential scale reduction statistic of all parameters estimated*

Description

Output the maximum potential scale reduction statistic of all parameters estimated

Usage

```
Calculate_Likelihood_test(train, test, paramG)
```

Arguments

<code>train</code>	a MutationFeatureData S4 class output of training data.
<code>test</code>	a MutationFeatureData S4 class output of test data.
<code>paramG</code>	an estimatedParameters S4 class with estimated parameters

Value

the likelihood of the test data

`convertFromTurbo_F`*Restore the converted parameter F for turboEM*

Description

Restore the converted parameter F for turboEM

Usage

```
convertFromTurbo_F(turboF, fdim, signatureNum, isBackground)
```

Arguments

<code>turboF</code>	F (converted for turboEM)
<code>fdim</code>	a vector specifying the number of possible values for each mutation signature
<code>signatureNum</code>	the number of mutation signatures
<code>isBackground</code>	the logical value showing whether a background mutaiton features is included or not

Value

a vector

convertFromTurbo_Q	<i>Restore the converted parameter Q for turboEM</i>
--------------------	---

Description

Restore the converted parameter Q for turboEM

Usage

```
convertFromTurbo_Q(turboQ, signatureNum, sampleNum)
```

Arguments

turboQ	Q (converted for turboEM)
signatureNum	the number of mutation signatures
sampleNum	the number of cancer genomes

Value

a vector

convertToTurbo_F	<i>Convert the parameter F so that turboEM can treat</i>
------------------	---

Description

Convert the parameter F so that turboEM can treat

Usage

```
convertToTurbo_F(vF, fdim, signatureNum, isBackground)
```

Arguments

vF	F (converted to a vector)
fdim	a vector specifying the number of possible values for each mutation signature
signatureNum	the number of mutation signatures
isBackground	the logical value showing whether a background mutaiton features is included or not

Value

a vector

convertToTurbo_Q	<i>Convert the parameter Q so that turboEM can treat</i>
------------------	--

Description

Convert the parameter Q so that turboEM can treat

Usage

```
convertToTurbo_Q(vQ, signatureNum, sampleNum)
```

Arguments

vQ	Q (converted to a vector)
signatureNum	the number of mutation signatures
sampleNum	the number of cancer genomes

Value

a vector

cv_PMSignature	<i>Output the maximum potential scale reduction statistic of all parameters estimated</i>
----------------	---

Description

Output the maximum potential scale reduction statistic of all parameters estimated

Usage

```
cv_PMSignature(inputG, Kfold = 3, nRep = 3, Klimit = 8)
```

Arguments

inputG	a MutationFeatureData S4 class.
Kfold	an integer number of the number of cross-validation folds.
nRep	an integer number of replications.
Klimit	an integer of the maximum value of number of signatures.

Value

a matrix of measures

Examples

```
load(system.file("extdata/sample.rdata", package = "selectKSigs"))
results <- cv_PMSignature(G, Kfold = 3)
```

getBG	<i>Get the status of using the background signature</i>
-------	---

Description

Get the status of using the background signature

Usage

```
getBG(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

the status of using the background signature

getCounts	<i>Get the count data in a matrix</i>
-----------	---------------------------------------

Description

Get the count data in a matrix

Usage

```
getCounts(object)
```

Arguments

object the MutationFeatureData class

Value

the count data in a matrix

getExposures	<i>Get a matrix of mutational exposures of signatures</i>
--------------	---

Description

Get a matrix of mutational exposures of signatures

Usage

```
getExposures(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

a matrix of mutational exposures of signatures

getFeatures	<i>Get a vector of possible features</i>
-------------	--

Description

Get a vector of possible features

Usage

```
getFeatures(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

a vector of possible features

getFeatureVec	<i>Get a matrix of feature vector list</i>
---------------	--

Description

Get a matrix of feature vector list

Usage

```
getFeatureVec(object)
```

Arguments

object the MutationFeatureData class

Value

a matrix of feature vector list

getK	<i>Get the number of signatures</i>
------	-------------------------------------

Description

Get the number of signatures

Usage

```
getK(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

the number of signatures in pmgetSignature in HiLDA

getLL	<i>Get the values of loglikelihood</i>
-------	--

Description

Get the values of loglikelihood

Usage

```
getLL(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

likelihood values estimated by pmgetSignature in HiLDA

getLogLikelihoodC	<i>Calculate the value of the log-likelihood for given parameters</i>
-------------------	---

Description

Calculate the value of the log-likelihood for given parameters

Usage

```
getLogLikelihoodC(
  vPatternList,
  vSparseCount,
  vF,
  vQ,
  fdim,
  signatureNum,
  sampleNum,
  patternNum,
  samplePatternNum,
  isBackground,
  vF0
)
```

Arguments

vPatternList	The list of possible mutation features (converted to a vector)
vSparseCount	The table showing (mutation feature, sample, the number of mutation) (converted to a vector)
vF	F (converted to a vector)
vQ	Q (converted to a vector)

fdim	a vector specifying the number of possible values for each mutation signature
signatureNum	the number of mutation signatures
sampleNum	the number of cancer genomes
patternNum	the number of possible combinations of all the mutation features
samplePatternNum	the number of possible combination of samples and mutation patternns
isBackground	the logical value showing whether a background mutaiton features is included or not
vF0	a background mutaiton features

Value

a value

getSamplelist	<i>Get the sample list</i>
---------------	----------------------------

Description

Get the sample list

Usage

```
getSamplelist(object)
```

Arguments

object the EstimatedParameters class (the result of pmgetSignature)

Value

the sample list of named elements.

getSamplelistG	<i>Get the sample list</i>
----------------	----------------------------

Description

Get the sample list

Usage

```
getSamplelistG(object)
```

Arguments

object the MutationFeatureData class

Value

the sample list of named elements.

getSignatures	<i>Get an array of signature feature distributions</i>
---------------	--

Description

Get an array of signature feature distributions

Usage

```
getSignatures(object)
```

Arguments

object	the EstimatedParameters class (the result of pmgetSignature)
--------	--

Value

an array of signature feature distributions

getTranscription	<i>Get the status of specifying the transcription bias</i>
------------------	--

Description

Get the status of specifying the transcription bias

Usage

```
getTranscription(object)
```

Arguments

object	the MutationFeatureData class
--------	-------------------------------

Value

the status of specifying the transcription bias

select_kth_fold	<i>Output the training data or test data</i>
-----------------	--

Description

Output the training data or test data

Usage

```
select_kth_fold(inputG, k, f_s, folds, include)
```

Arguments

inputG	a MutationFeatureData S4 class output by the pmsignature.
k	an integer number of the number of cross-validation folds.
f_s	a primary key of combining the feature pattern and sample ID.
folds	the assignment to each fold.
include	a boolean indicator of whether to include kth fold or not.

Value

a MutationFeatureData S4 class of either include or exclude kth fold.

splitG	<i>Output the maximum potential scale reduction statistic of all parameters estimated</i>
--------	---

Description

Output the maximum potential scale reduction statistic of all parameters estimated

Usage

```
splitG(inputG, Kfold = 3)
```

Arguments

inputG	a MutationFeatureData S4 class output by the pmsignature.
Kfold	an integer number of the number of cross-validation folds.

Value

a matrix made of perplexity from the results of cross-validation.

Examples

```
load(system.file("extdata/sample.rdata", package = "selectKSigs"))
G_split <- splitG(G, Kfold = 3)
```

Index

calcPMSLikelihood, [2](#)
Calculate_Likelihood_test, [3](#)
convertFromTurbo_F, [3](#)
convertFromTurbo_Q, [4](#)
convertToTurbo_F, [4](#)
convertToTurbo_Q, [5](#)
cv_PMSignature, [5](#)

getBG, [6](#)
getCounts, [6](#)
getExposures, [7](#)
getFeatures, [7](#)
getFeatureVec, [8](#)
getK, [8](#)
getLL, [9](#)
getLogLikelihoodC, [9](#)
getSamplelist, [10](#)
getSamplelistG, [10](#)
getSignatures, [11](#)
getTranscription, [11](#)

select_kth_fold, [12](#)
splitG, [12](#)