

# PPM

A modulation technique for high speed wireless systems  
by Jan Boer, Lucent Technologies

Lucent Technologies  
Bell Labs Innovations



page 1

## NOTICE

- This document has been prepared by Lucent Technologies Nederland B.V. ("Lucent") to assist the Standards Working Group IEEE P802.11. It is proposed to the Working Group as a basis for discussion and is not to be construed as a binding proposal on Lucent. Lucent specifically reserves the right to amend or modify the material contained herein and nothing herein shall be construed as conferring or offering licenses or rights with respect to any intellectual property of Lucent.

Jan Boer, Lucent Technologies, November 1997

page 2

## Goals for higher speed in ISM band

- Raw bitrate 8-10 Mbit/s
- Comply to FCC rules
  - 10 dB processing gain (in case of Direct Sequence)

Jan Boer, Lucent Technologies, November 1997

page 3



## Performance criteria

- Coverage
  - Not more than 10 dB sensitivity drop compared to 802.11
- Delay spread
  - office 50 ns
  - retail up to 200 ns
  - industrial > 200 ns

Jan Boer, Lucent Technologies, November 1997

page 4



## Compatibility goals

- interoperable / coexistence with current 802.11

Jan Boer, Lucent Technologies, November 1997

page 5



## What is PPM


- PPM is Puls Position Modulation based on the current Direct Sequence technology using the 11-chip Barker Sequence.
- Occupying same bandwidth PPM makes high speed possible:
  - 5, 8, 10 or 11 Mbit/s
- Developed at Bell Labs

Jan Boer, Lucent Technologies, November 1997

page 6



## Current 802.11 2 Mbit/s system



Information Rate = 1 bit/symbol/quadrature component = 2 bits/symbol


Chips: 11 (essentially) orthogonal positions due to Barker code

Note: only a single position (out of the 11) is used

Jan Boer, Lucent Technologies, November 1997

page 7

## Use 8 out of 11 positions




Example: Number of positions,  $M = 8$   
 $K = \log_2 M = 3$  bits/symbol

Jan Boer, Lucent Technologies, November 1997

page 8

## Barker Code Pulse Position Modulation




Jan Boer, Lucent Technologies, November 1997

page 9


## PPM Principals

### Disjoint Quadrature PPM



**M ways to choose each (I&Q) channel**  
**P polarities per channel choice**  
**Number of possible configurations:**  
 $N = M * M * P * P$   
 $M = 8, P = 2 \quad N = 256; \quad 8 \text{ bits/symbol}$

### Joint Quarternary PPM




**M ways to choose both I&Q channels**  
**4 polarities.**  
 $N = M * 4 = 8 * 4 = 32 \rightarrow 5 \text{ bits/symbol}$

Jan Boer, Lucent Technologies, November 1997

page 10


How to increase datarate



\* 3 positions not used by ppm



10 Mbit/s



.818 micro second  
symbol time



page 13

page 14


## Optimum MLSE Receiver

- Derivation of Optimum Receiver in
  - Barker Code Position Modulation for High-Rate Communication in the ISM Band
 Israel Bar David and Rajeev Krishnamoorthy  
 Bell Labs Technical Journal, Autumn 1996
- Function to compensate Cross Rail Interference, Side Lobes, ISI
- PPM makes reduction of complexity possible at moderate costs

Jan Boer, Lucent Technologies, November 1997

page 15

## Receiver complexity



CPE channel parameter estimator  
 CMF channel matched filter

Jan Boer, Lucent Technologies, November 1997

page 16



## Receiver Functions: Channel Matched Filter

- Concentrate all energy
- Gives optimal sample timing
- Estimation of the channel parameters needed
  - many well-known methods
  - can be achieved during training
    - on preamble

Jan Boer, Lucent Technologies, November 1997

page 17



## Receiver Functions: Tentative Symbol Estimator

- With knowledge of channel TSE removes cross rail interference for all possible symbols (actually 256, in essence 64 because polarity is not contributing to complexity)
- Due to autocorrelation properties of Barker sidelobes can initially be ignored (mode sifter can take care)
- Estimates N most likely symbols (N=4)

Jan Boer, Lucent Technologies, November 1997

page 18



## Receiver Functions: Mode Sifter

- Reduced state trellis structure sifting the tentatively retained modes (maxima of TSE)
- Calculates path metric taking ISI and sidelobs into account
- Trellis path determines final estimate
  - path depth of 4 is sufficient

Jan Boer, Lucent Technologies, November 1997

page 19



## Reduced complexity receiver

- Implementation specific
- Manufacturer choice
- At the cost of some performance
- Gatecount in order of 2-3 times current 802.11

Jan Boer, Lucent Technologies, November 1997

page 20



## Performance


- Parameters
  - Packet error rate
    - 100 bytes packets
  - SNR
  - Time delay spread
    - 0, 50, 100, 200 ns

Jan Boer, Lucent Technologies, November 1997

page 21

### Performance of 8 Mbit/s

**Moderate complexity  
receiver:  
CMF, TSE and MS**




Jan Boer, Lucent Technologies, November 1997

page 22

Performance of  
8 Mbit/s

Low complexity  
receiver (CMF only)



Jan Boer, Lucent Technologies, November 1997



PPM Performance

Bitrate	FER   TDS >	0 ns	50 ns	100 ns	200 ns
5 TSE+MS	10-2	22	20	20	19
	10-1	16	16	16	15
5 CMF only	10-2	22	20	17	25
	10-1	17	16	15	16
8 TSE+MS	10-2	24	24	21	23
	10-1	13	13	13	13
8 CMF only	10-2	26	x	x	x
	10-1	19	22	x	x
10 TSE+MS	10-2	22	24	30	x
	10-1	18	18	18	x
11 TSE+MS	10-2	24	29	x	x
	10-1	18	19	23	x

SNR

Jan Boer, Lucent Technologies, November 1997

page 24



## Performance Highlights

- For 5 and 8 Mbit/s a delayspread of 200ns is no problem for a reduced complexity Rx
- 8 Mbit/s with simple Rx (CMF only) will tolerate 50-70 ns (at FER 10<sup>-1</sup>)
- 5 Mbit/s with simple RX can handle at least 100ns
- 10 and 11Mbit/s can handle 100 ns (at FER 10<sup>-1</sup>)

Jan Boer, Lucent Technologies, November 1997

page 25



## Sensitivity

- 5 Mbit/s PPM loses compared to 2 Mbit/s 802.11 only 0.5dB
- 8 Mbit/s PPM 3.5dB
- 10, 11 Mbit/s in same order as 8 Mbit/s

Jan Boer, Lucent Technologies, November 1997

page 26



## PPM and FCC

- 8 Mbit/s approved by FCC
- 10/11 there is a risk (increasing symbol rate)
- Higher rate in PPM is also possible using QAM (16 QAM gives 10 Mbit/s)
- QAM is certainly acceptable by the FCC (performance penalty)

Jan Boer, Lucent Technologies, November 1997

page 27



## Comparison to Walsh Code Modulation


- Performed same simulation with Harris Walsh code proposal
- BER and FER was simulated for framelength 100 bytes
- Low complexity receiver, perfect timing and phase sync assumed.

Jan Boer, Lucent Technologies, November 1997

page 28



## Performance of Walsh code (Harris proposal)



a) Irreducible packet error ratio versus delay spread for a packet size of 100 symbols or 800 bits,  
b) irreducible bit error ratio, both for exponentially decaying Rayleigh fading channels.

Jan Boer, Lucent Technologies, November 1997

page 29

## Can Walsh be made more robust?

- Delayspread above 30 ns (10% FER) is problem
- Equalizer---> very complex, less performance (noise enhancement)
- maximum likelihood sequence estimation techniques similar to ppm?
  - can not split MLSE into 2 components (TSE and Mode sifter) due to large cross correlations of all Walsh codes
  - Walsh sidelobs are high, can not be ignored in TSE to get moderate complexity

Jan Boer, Lucent Technologies, November 1997

page 30

## Finally Walsh has compliance issue with FCC

- Meets jammer test
- Does not meet the 'required' spreading code of 10 chips

Jan Boer, Lucent Technologies, November 1997

page 31



## Preamble

- PPM is Barker sequence based and can train on 802.11 DS preamble (192 microseconds)
- Shorter preamble is possible.
  - 24 microseconds for Rx training (synchronization, channel matched filter)
  - + time for energy detection and possibly antenna diversity
  - + time to send over header info at higher rate
  - total preamble time needed in the order of 50 microseconds

Jan Boer, Lucent Technologies, November 1997

page 32





## Coexistence and interoperability issues

- With long 802.11 header PPM is fully coexistence and interoperable (can fall back to 1 and 2 Mbit/s)
- If 20 micros slottime is maintained also with a short header coexistence and/or interoperability is possible

Jan Boer, Lucent Technologies, November 1997

page 33



## Possible coexistence scenario

- mix 1/2 Mbit/s with long preamble and PPM with short preamble
  - 1/2 Mbit detects short preamble (carrier)
    - waits for SFD; not found
    - defers until energy or carrier drop
  - PPM can detect long preamble
- long/short can be made to defer for each other

Jan Boer, Lucent Technologies, November 1997

page 34



## Possible interoperability scenario

- PPM with both short and long header
  - receiver has to detect short or long (short header different from scrambled ones)
- In high speed network run short header
- falls back to long header if appropriate

Jan Boer, Lucent Technologies, November 1997

page 35



## Conclusion

- PPM the way to go for higher speed in ISM band
- 5,8,10,11 Mbit/s
- high performance with moderate complexity receiver
- receiver complexity implementers choice
- FCC approved

Jan Boer, Lucent Technologies, November 1997

page 36



## Conclusion con't

- Works fine with IEEE802.11 preamble
  - standardization effort minimal, just adds an annex
- PPM is not dependent on current IEEE preamble
  - throughput increase by defining short preamble
  - interoperability and coexistence possible

Jan Boer, Lucent Technologies, November 1997

page 37

